

ZIITEK ELECTRONIC MATERIAL & TECHNOLOGY CO..LTD

TIF700Q Series Thermally Conductive Silicone Pads Series

Gray

Ceramic filled silicone elastomer

1.0mm to 10.0mm

60 Shore 00

3.48g/cc

-40 ~160 °C

5.5 KV

4. 5 MHz

5.2X10¹³ Ohm-meter

8.0 W/mK

8.0 W/mK

0.30%

UL94 V0

Visual ******

ASTM D374

ASTM D2240

ASTM D297

ASTM D149

ASTM D150


ASTM D257

ASTM D5470

GB-T32064

ASTM E595

UL E331100



Typical Properties of TIF700Q Series




Features

- Sood thermal conductivity: 8.0 W/mK
- » Naturally tacky needing no further adhesive coating
- » Soft and Compressible for low stress applications
- » Available in varies thickness

Application

- Cooling components to the chassis of frame
- Set Top Box
- » Car Battery & Power Supply
- Charging Pile
- » LED TV/ Lighting

kg. vs.Thermal Resistance



Psi. vs. Compression Ratio

Color

Construction

Hardness

Thickness range

Specific Gravity

Operating Temp

Volume Resistivity


Outgassing (TML)

Flame Rating

Thermal Conductivity

Dielectric Breakdown Voltage

Dielectric Constant@1MHz



Product Specification


Product Thicknesses

0.040-inch to 0.400-inch (10.0mm to 10.0mm)

Product Sizes

10" x 16"(254mm x406mm) Individual die cut shapesand and custom thickness can be supplied. Please contact us for confirming.

Product Identification:



Thermally Conductive Materials **Heat Generating Materials** Thermally Conductive Plastics Foaming Silica Gel **Die-Cutting Products**

Canada:

Tel:+001-604-2998559 E-mail: sales@thermazig.com

China: Tel: +86-769-38801208 E-mail: jor@ziitek.com

Taiwan:

Tel:+886-2-22771007 E-mail:frances@ziitek.com.tw



http://www.ziitek.com